

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
21 April 2005 (21.04.2005)

PCT

(10) International Publication Number  
**WO 2005/035291 A1**

(51) International Patent Classification<sup>7</sup>: **B60K 15/067**,  
15/07

(74) Agents: NAKAJIMA, Jun et al.; TAIYO, NAKAJIMA &  
KATO, Seventh Floor, HK-Shinjuku Bldg., 3-17, Shinjuku  
4-chome, Shinjuku-ku, Tokyo 1600022 (JP).

(21) International Application Number:  
PCT/JP2004/015105

(22) International Filing Date: 6 October 2004 (06.10.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
2003-348059 7 October 2003 (07.10.2003) JP

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CO,  
CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB,  
GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP,  
KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK,  
MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL,  
PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR,  
TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(71) Applicant (for all designated States except US): TOY-  
OTA JIDOSHA KABUSHIKI KAISHA [JP/JP]; 1, Toy-  
ota-cho, Toyota-shi, Aichi 4718571 (JP).


(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,  
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).

(72) Inventor; and

(75) Inventor/Applicant (for US only): MINAMI, Teruyuki  
[JP/JP]; c/o TOYOTA JIDOSHA KABUSHIKI KAISHA,  
1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP).

[Continued on next page]

(54) Title: FUEL TANK SUPPORTING STRUCTURE



(57) Abstract: Fuel tanks (52, 54, 56) are disposed in parallel along a vehicle transverse direction on a rear sub frame (40). The fuel tank (54) is placed on fuel tank supporting brackets (62) which span between a cross rail (46) and a cross rail (48) of the rear sub frame (40). In a case in which an impact load F1 is applied to the fuel tank (56), the fuel tank (56) abuts a rear cross member (20), and upward movement is impeded. Therefore, weak portions (70) of the fuel tank supporting brackets (62) break, and the fuel tank (54) limitedly moves toward a bottom of a vehicle body.

WO 2005/035291 A1

**Published:**

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*